

*See attachment no field investigation*

DEPARTMENT OF TRANSPORTATION  
FEDERAL RAILROAD ADMINISTRATION

REPORT FOR (month/year)  
**February, 1995**

**FALSE PROCEED SIGNAL REPORT**

DATE **February 28, 1995**

All railroads subject to Regulations of the Federal Railroad Administration shall submit a false proceed signal report, original only, to the Federal Railroad Administration within five days after a false proceed occurs. If no false proceed occurs during any calendar month, a report showing "No Failures" must be filed within ten days after the end of the month.  
Copies of this form will be furnished upon request to the Department of Transportation, Federal Railroad Administration, Office of Safety, Washington, D.C. 20590

REPORTING CARRIER (railroad & region or division)  
**CSX Transportation**  
**- System -**

MAIL TO

Director of Railroad Safety  
 Federal Railroad Administration  
 Suite 440, North Tower  
 1720 Peachtree Road, NW  
 Atlanta, Georgia 30309

REPORTING OFFICER (signature/title)  
**Chief Engr.-Train Control**

A failure should not be counted more than one time in items 1, 2, 3, and 4; the failure should be classified under the basic system or appliance of which it forms an essential part. E.g.; assume grounds cause a block signal to indicate a false proceed causing corresponding indications of a cab signal system on each train approaching this point, such failures should be included in item 1, Block Systems.  
A false proceed failure is a failure of a system, device or appliance to indicate or function as intended which results in less restriction than intended.

- The following abbreviations may be used in the report.
- A—Automatic
  - AB—Automatic block
  - ACS—Automatic cab signal
  - APB—Absolute permissive block
  - ATC—Automatic train control
  - ATS—Automatic train stop
  - CL—Color light
  - CPL—Color position light
  - E—Electric
  - EM—Electromechanical
  - EP—Electropneumatic
  - FP—False proceed
  - MB—Manual block
  - M—Mechanical
  - P—Pneumatic
  - PL—Position light
  - SA—Semiautomatic
  - TC—Traffic control

TYPE OF SYSTEM	DATE	LOCOMOTIVE NUMBER	DEVICE THAT FAILED	LOCATION (city and state)
1 BLOCK SYSTEMS <input type="checkbox"/> AB <input type="checkbox"/> APB <input checked="" type="checkbox"/> TC	2/12/95	Train Q67611	None	Atlanta, GA
2 INTERLOCKING <input type="checkbox"/> REMOTE <input type="checkbox"/> AUTO-MATIC <input type="checkbox"/> MANUAL				
3 AUTOMATIC SYSTEMS <input type="checkbox"/> ATS <input type="checkbox"/> ATC <input type="checkbox"/> ACS				
4 OTHER (specify)				

**NATURE AND CAUSE OF FAILURE/CORRECTIVE ACTION TAKEN**

On February 12, 1995, Train Q67611 alleged having lunar over red indication at signal 10 at top of slide, and then to dark over red, this route was not requested at this time. Signal system was removed from service.  
Signal person performed all required operational tests. It was determined that signal system was functioning as indicated. Signal system is restored to service.

(If more space is required, continue on reverse)