

DEPARTMENT OF TRANSPORTATION
FEDERAL RAILROAD ADMINISTRATION
 FALSE PROCEED SIGNAL REPORT

REPORT FOR (month/year)

March 1997

DATE

April 2, 1997

All railroads subject to Regulations of the Federal Railroad Administration shall submit a false proceed signal report, original only, to the Federal Railroad Administration within five days after a false proceed occurs. If no false proceed occurs during any calendar month, a report showing "No Failures" must be filed within ten days after the end of the month.

Copies of this form will be furnished upon request to the Department of Transportation, Federal Railroad Administration, Office of Safety, Washington, D.C. 20590.

REPORTING CARRIER (railroad & region or division)

Union Pacific Railroad
 1416 Dodge Street
 Omaha, Nebraska
 Kansas City Service Unit

MAIL TO

Director of Railroad Safety
Federal Railroad Administration
 City Center Square, Suite 1130
 1100 Main Street
 Kansas City, MO 64105-2112

FEDERAL RAILROAD
 ADMINISTRATION

97 APR -7 A8:54

REPORTING OFFICER (signature/title)

Chief Engineer-Signals

The following abbreviations may be used in the report:

A failure should not be counted more than one time in items 1, 2, 3, and 4; the failure should be classified under the basic system or appliance of which it forms an essential part. E.g.; assume grounds range a block signal to indicate a false proceed causing corresponding indications of a cab signal system on each train approaching this point, such failures should be included in item 1, Block Systems.

A false proceed failure is a failure of a system, device or appliance to indicate or function as intended which results in less restriction than intended.

- A = Automatic
- AB = Automatic block
- ACS = Automatic Cab Signal
- APB = Absolute permissive block
- ATC = Automatic train control
- ATS = Automatic train stop
- CL = Color light
- CPL = Color position light
- E = Electric
- EM = Electromechanical
- EP = Electropneumatic
- FP = False proceed
- MB = Manual block
- M = Mechanical
- P = Pneumatic
- PL = Position light
- SA = Semiautomatic
- TC = Traffic Control

TYPE OF SYSTEM	DATE	LOCOMOTIVE NUMBER	DEVICE THAT FAILED	LOCATION(city and state)
1 BLOCK SYSTEMS <input type="checkbox"/> AB <input type="checkbox"/> APB <input checked="" type="checkbox"/> TC	3/21/97	UP9453	NONE	Kansas City, Missouri
2 INTERLOCKING <input type="checkbox"/> AUTOMATIC <input type="checkbox"/> REMOTE <input type="checkbox"/> MANUAL				
3 AUTOMATIC SYSTEMS <input type="checkbox"/> ATS <input type="checkbox"/> ATC <input type="checkbox"/> ACS				
4 OTHER (Specify)				

NATURE AND CAUSE OF FAILURE/CORRECTIVE ACTION TAKEN

On March 21, 1997, at 17:50 CST on the Kansas City Terminal Subdivision, CRMWL-20 was east bound stopped on Track No. 2 across the insulated joints occupying both the east and west track circuits at the intermediate signal location at Mile Post 280.4. The westbound signal at Mile Post 280.4 was observed displaying a yellow over lunar.

An investigation revealed the signal cabin at Mile Post 280.4 had been hit and knocked a foot off center dumping all the relays in the house.

The relays were all righted, the signal system was restored to proper operation, and all applicable tests were performed.

(If more space is required, continue on reverse)